



CROCHET
SKILL LEVEL
INTERMEDIATE

Designed by Quayln Stark

What you will need:

RED HEART® Hygge Charm: 2 balls 6631 Morning Star

Susan Bates® Crochet Hook: 5.75mm [US J-10]

Yarn needle, stitch markers

GAUGE: 12 sts = 4" (10 cm); 14 rows = 4" (10 cm). **CHECK YOUR GAUGE.** Use any size hook to obtain the gauge given.



RED HEART® Hygge Charm™, Art E882 available

in 7 oz (198 g), 432 yd (395 m) balls



Cabled Hooded Cowl

Want to keep warm, but don't like the bulkiness of scarves? This hooded cowl is the answer! It fits under most jackets and the hood will keep the wind out, too. With the subtle shimmer of Hygge Charm and the beautiful crochet cable pattern, this project will help you stand out in the crowd.

Cowl measures 30" (76 cm) across and 20" (51 cm) tall.

Special Stitches

Back Post Double Crochet (BPdc) =

Yarn over, insert hook from back of work to front and to back again around post of indicated stitch; yarn over and pull up a loop (3 loops on hook), [yarn over and draw through 2 loops on hook] twice.

Front Post Double Crochet (FPdc) =

Yarn over, insert hook from front of work to back and to front again around post of indicated stitch; yarn over and pull up a loop (3 loops on hook), [yarn over and draw through 2 loops on hook] twice.

Front Post Treble Crochet (FPtr) = Yo twice, insert hook from front of work to back and to front again around post of indicated stitch; yo and pull up a loop, [yo and draw through 2 loops on hook] 3 times.

Forward Cable (fwd cable) = Skip each of the next 2 post sts and next 2 sc, FPtr around each of the next 2 post sts, working in front of the post sts just made, FPtr around each skipped post st.
Backward Cable (bwd cable) = Skip each of the next 2 post sts and next 2 sc, FPtr around each of the next 2 post sts, working behind the post sts just made, FPtr around each of the 2 skipped post sts.

SIDE PANELS (make 2)

Ch 36.

Row 1: Sc in 2nd ch from hook and in each ch across, ch 1, turn - 35 sc.

Row 2: Sc in each st, ch 1, turn.

Rows 3-35: Repeat Row 2.

Row 36: 2 sc in 1st st, sc in each st across to last st, 2 sc in last st, ch 1, turn - 37 sc.

Row 37: Sc in each st, ch 1, turn.

Rows 38-79: Repeat Rows 36-37.

Row 80: 2 sc in 1st st, sc in each st across to last st, 2 sc in last st - 81 sc. Fasten off.



BACK CABLING

Make an adjustable ring as follows:

Wrap yarn around your finger with the yarn tail to the left and under the working yarn. Insert hook through the circle from front to back. Using the working yarn, yarn over and pull up a loop.

Row 1: Ch 1, (2 sc, 2 dc, 2 sc) in adjustable ring, ch 1, turn; tighten beginning yarn tail to close adjustable ring.

Row 2: Sc in first 2 sts, BPdc in next st, 2 sc between 2 dc of last row, BPdc in next st, sc in last 2 sts, ch 1, turn.

continued...



2015 - 2018
WOMEN'S CHOICE AWARD™
AMERICA'S MOST RECOMMENDED
YARN BRAND

SHOP KIT

Row 3: Sc in first 2 sts, *2 FPdc in BPdc of last row, sc in next 2 sts; repeat from * once, ch 1, turn.

Row 4: Sc in first 2 sts, *BPdc, sc between 2 FPdc of last row, BPdc, sc in next 2 sts; repeat from * once, ch 1, turn.

Row 5: Sc in first 2 sts, *FPdc, 2 sc in next st, FPdc, sc in next 2 sts; repeat from * once, ch 1, turn.

Row 6: Sc in first 2 sts, BPdc, sc in next 2 sts, [2 BPdc in FPdc of last row, sc in next 2 sts] twice, BPdc, sc in next 2 sts, ch 1, turn.

Row 7: Sc in first 2 sts, 2 FPdc in BPdc of last row, sc in next st, 2 sc in next st, fwd cable, 2 sc in next st, sc in next st, 2 FPdc in BPdc of last row, sc in last 2 sts, ch 1, turn.

Place marker on both sides of Row 7.

Row 8: Sc in first 2 sts, BPdc in next 2 sts, sc in next 2 sts, BPdc in next 2 sts, 2 sc in middle of fwd cable of last row, BPdc in next 2 sts, sc in next 2 sts, BPdc in next 2 sts, sc in last 2 sts, ch 1, turn.

Row 9: Sc in 1st st, 2 sc in next st, bwd cable, [2 sc in next st] twice, bwd cable, 2 sc in next st, sc in next st, ch 1, turn.

Row 10: Sc in first 2 sts, *BPdc in next 2 sts, 2 sc in middle of bwd cable of last row, BPdc in next 2 sts, sc in next 2 sts; repeat from * once, ch 1, turn.

Row 11: Sc in first 2 sts, *FPdc in next 2 sts, sc in next 2 sts; repeat from * 3 times, ch 1, turn.

Row 12: Sc in first 2 sts, *BPdc in next 2 sts, sc in next 2 sts; repeat from * 3 times, ch 1, turn.

Rows 13-14: Repeat Rows 9-10.

Row 15: Sc in first 2 sts, FPdc in next 2 sts, sc in next st, 2 sc in next st, fwd cable, 2 sc in next st, sc in next st, FPdc in next 2 sts, sc in last 2 sts, ch 1, turn.

Rows 16-119: Repeat Rows 8-15.

Row 120: Repeat Row 8.

Row 121: Sc in first 2 sts, *FPdc in next 2 sts, sc in next 2 sts; repeat from * 3 times, ch 1, turn.
Fasten off.

FINISHING

With wrong sides facing, seam Side Panels together using a single crochet join, starting at either center point and seaming to first corner (see **A** on page 4).

Place the Back Cabling between the two side panels on the side opposite the Side Panel join. Align the pointed end of Side Panels with the marked Row 7 of Back Cabling. Seam along both sides of the cabling with a sc join, leaving an opening for the hood (see **B** on page 4).

Hood Edging

Slip st in any st around the hood between seams **A** and **B**. Ch 1, work 1 sc in each st around; slip st in 1st sc to join. Fasten off.

Bottom Edging

Slip st in any st around bottom edge. Ch 1, sc in each st around to 1st center point, *4 sc in same st in center point, sc in each st to next point; repeat from * to last st, slip st in 1st sc to join. Fasten off.

Weave in all loose ends.

ABBREVIATIONS

ch = chain; **dc** = double crochet; **sc** = single crochet; **st(s)** = stitch(es); *** or **** = repeat whatever follows the * or ** as

See next two pages for schematics and alternate photos





